

Charand Chak Mose To Kosevice

Schedule XLV-Form No. 134

M13 ND 707

M12-3054 m
Executive Engineer
Rural Works Department
Works Div. Marhaura

DIVISION

SUB-DIVISION

Measurement Book

Lajam Kumar

(These four lines should be repeated at the commencement of the measurement relating to each work)

Continuation

Sch. XLV-Form No. 134

Particulars	Details of actual measurement				Contents of area
	No.	L.	B.	D.	
<u>Abstract of Cost</u>					
<u>S.No.01:- Clearing and grubbing</u>					
Road land (By manual					
means) including uprooting					
wild vegetation etc.					
Vide P.No. 01 in T.Y.B.					
0.742 Hec ea - 49496 = 70 Rs - 36727 = ∞					
<u>S.No.02:- Construction of Subgrade</u>					
and earthen shoulders					
with approved material					
obtained from Govt. pits					
et - Comp J.C.					
Vide P.No.02 in T.Y.B.					
1122.30 y ² Rs - 176 = 96 Rs - 198602 = ∞					
<u>S.No.03:- Construction of granular</u>					
Subbase by spreading					
well graded material					
spreading et - C.P. etc.					
Vide P.No. 04 in T.Y.B.					
78.219 y ² Rs - 2208 = 12 Rs - 172717 = ∞					
<u>S.No.04:- Paving layer spreading</u>					
and compacting stone aggregate					
of specific size etc.					
Vide P.No. 06 in T.Y.B.					
75.948 y ² Rs - 4081 = 20 Rs - 309959 = ∞					
Continuation					R-718005 = ∞

Particulars	Details of actual measurement				Contents of area
	No.	L.	B.	D.	
				R	718005=00
J. NO. 05:-	Providing laying, spreading and compacting stone aggregates of specific sizes to water bound macadam specification				
	et - Comp - 7-6.				
	Vide P. NO. 09 in T. 4. B.				
	113.669	4	20	32	415383=00
J. NO. 06:-	Prime Coat (two portions)				
	Providing and applying Prime Coat with bitumen emulsion (SS-1) on prepared surface et - complete				
	Vide P. NO. 10 in T. 4. B.				
	1515.58	4	20	41	62366=00
J. NO. 7:-	Providing applying tack Coat with bitumen emulsion (RS-1) using emulsion et - complete				
	Vide P. NO. 11 in T. 4. B.				
	1714.314	4	20	13	23932=00
J. NO. 8:-	Providing laying and bedding of close graded premix surfacing material of 20mm max. Comp. size 13.20mm.				

Continuation

R-1219686=00

Particulars	Details of actual measurement				Contents of area
	No.	L.	B.	D.	
					R-1219686=00
					to 0.70 mm (Type B)
					et- Comp + G.
					Vide P. No. 11 in T.Y.B.
					1714.3194 ² ER - 219 = 294 ² R - 375932=00
S.No. 09:-					Providing and applying
					Jack Coat with Githon
					emulsion (RS-1) using
					emulsion distributor
					et- Comp + G.
					Vide P. No. 13 in T.Y.B.
					13912.50 M ² ER 11=71 4 ² R 162915=00
S.No. 10:-					Providing and Laying
					Some dense Githonous
					Concrete with 100-120 TPH
					batch type H.M.P. pump
					an coverage et fl.
					Vide P. No. 13 in T.Y.B.
					347.81 4 ² R - 10737 = 604 ³ R - 3734644=00
S.No. 11/17					Providing 2 layers of
					Hot applied thermoplastic
					Compound 2.50 mm thick
					including reflecting et fl.
					Vide P. No. 13 in T.Y.B.
					696.00 4 ² R - 735 = 40 4 ² R - 511838=00

Continuation

R-6005015=00

Continuation