

Continuation

Particulars	Details of actual measurement				Contents of area
	No.	L.	B.	D.	
J.No.02: Construction of granular					
Sub base layer providing					
well graded material					
Spreading at - Compd.					
6x30x4.05x					
6x 30x 4.05x 0.15 = 109.35					
1x 4x 4.05x 0.15 = 2.40					
4x 30x 4.05x 0.15 = 72.90					
1x 28x 4.05x 0.15 = 17.01					
					201.664 ³
J.No.03: WB4 Garku PI (Buckhead					
moors) Providing (in my space)					
and Compacting of sub					
6x 30x 3.75x 0.075 = 50.625					
1x 4x 3.75x 0.075 = 1.125					
4x 30x 3.75x 0.075 = 33.75					
1x 28x 3.75x 0.075 = 7.875					
					93.375 ⁴
J.No.04: Prime Coat (low portion)					
Providing (in my space) and supplying					
93.375					
0.075					
					1245.004 ²
J.No.05: Tack Coat - Providing					
applying tack coat with Citrus					
emulsion (R-1) at 1/6					
S. Quantity J.No.04 = 1245.00					

Continuation

Material Statement :-	
(1) Bore - 330-308 y ³ -	
(1) 53-950 m - 129.06 y ³ R ₂ -	
(2) 950-236 m - 51.75 y ³ R ₂ -	
(3) 236 m Co/Cu - 77.30 y ³ R ₂ -	
(4) 53-2240 y ³ - 112.98 y ³ R ₂ -	
(5) Type B-11200 - 22.41 y ³ R ₂ -	
(6) Cores/Stone - 34-22 y ³ R ₂ -	

[Signature]
10/10/20

Bitumen Statement	
(1) Bitumen emulsion (SS-1) - 1.058 y ³ -	
(2) Bitumen emulsion (RS-1) - 0.342 y ³ -	
(3) Bitumen (S-90) - 2.365 y ³ -	

Continued

[illegible]