

החל ב- 19.2.24 והמשיך עד 19.2.24  
מס' 100 מ' קוטר מ' קוטר מ' קוטר  
מ' קוטר מ' קוטר מ' קוטר  
מ' קוטר מ' קוטר מ' קוטר  
מ' קוטר מ' קוטר מ' קוטר  
מ' קוטר מ' קוטר מ' קוטר

19.2.24

Executive Engineer  
RWD Works Division

19.2.24

Sch. XLV - Form No. 134

R.W.D. PARIPATANA DIVISION

R.W.D. PATANA SUB-DIVISION

## Measurement Book

No.

1439

Name \_\_\_\_\_

Date of first entry \_\_\_\_\_

Date of last entry \_\_\_\_\_







| Particulars                         | Details of actual measurement |         |         |       | Contents of area |
|-------------------------------------|-------------------------------|---------|---------|-------|------------------|
|                                     | No.                           | L       | B       | D     |                  |
| 9.5 S/F and Placing HYSD bar        |                               |         |         |       |                  |
| Reinforcement for $A_1 - A_2 + P_2$ |                               |         |         |       |                  |
| Main girder and cross girder        |                               |         |         |       |                  |
| in buyer - 16 - 80 - all comp.      |                               |         |         |       |                  |
| 155.                                |                               |         |         |       |                  |
| Main Girders.                       |                               |         |         |       |                  |
| 28mm $\phi$ -                       | 18X                           | 20.46X  | @4.84 = |       | 1782.48 kg       |
|                                     | 10X                           | 20.46X  | @4.84 = |       | 990.26 "         |
|                                     | 6X                            | 21.928X | @4.84 = |       | 636.79 "         |
|                                     | 4X                            | 20.162X | @4.84 = |       | 370.34 "         |
|                                     | 4X                            | 17.862X | @4.84 = |       | 345.81 "         |
|                                     | 4X                            | 15.404X | @4.84 = |       | 298.22 "         |
|                                     | 4X                            | 12.944X | @4.84 = |       | 250.60 "         |
|                                     |                               |         |         |       |                  |
|                                     | 2X                            | 21.770X | @4.84 = |       | 210.73 "         |
|                                     | 2X                            | 19.162X | @4.84 = |       | 185.49 "         |
|                                     | 2X                            | 15.704X | @4.84 = |       | 152.01 "         |
|                                     |                               |         |         |       |                  |
| 16mm $\phi$ -                       | 11X                           | 8.388X  | @0.62 = |       | 53.01 "          |
|                                     | 6X                            | 19.24X  | @1.58 = |       | 182.40 "         |
|                                     | 6X                            | 19.26X  | @1.58 = |       | 182.58 "         |
|                                     | 66X                           | 19.26X  | @0.22 = |       | 279.66 "         |
|                                     | 6X                            | 19.27X  | @0.22 = |       | 25.44 "          |
|                                     |                               |         |         |       |                  |
| 10mm $\phi$ -                       | 146X                          | 8.312X  | @0.62 = |       | 752.40 "         |
|                                     | 36X                           | 8.56X   | @0.62 = |       | 191.06 "         |
|                                     | 195X                          | 1.558X  | @0.62 = |       | 188.36 "         |
|                                     | 83X                           | 8.328X  | @0.62 = |       | 428.56 "         |
|                                     | 18X                           | 8.576X  | @0.62 = |       | 95.71 "          |
|                                     |                               |         |         |       |                  |
|                                     |                               |         |         | C.O = | 7568.90 kg       |

Continuation











| Particulars                                            | Details of actual measurement |                             |          |                          | Contents of area |
|--------------------------------------------------------|-------------------------------|-----------------------------|----------|--------------------------|------------------|
|                                                        | No.                           | L.                          | B.       | D.                       |                  |
| RB 1 →                                                 | 2X                            | 35.00X                      | 35.00X   | 6.00=                    | 14700 = 104      |
| RB 2 →                                                 | 3X                            | 35.00X                      | 35.00X   | 6.00=                    | 22050 = 104      |
|                                                        |                               |                             |          |                          | 36,750 = 104     |
|                                                        |                               | <del>1000</del><br>10103/26 |          | <del>2</del><br>12-03-28 |                  |
|                                                        |                               | J.E                         |          | A.E                      |                  |
| 14. > P/V and laying POT-PTFE                          |                               |                             |          |                          |                  |
| Bearing AB-A <sub>1</sub> -D <sub>0</sub> -all comp.   |                               |                             |          |                          |                  |
| Job                                                    |                               |                             |          |                          |                  |
|                                                        |                               | 3X                          | 250 =    | 750 T                    |                  |
| 15. > P/V and laying POT-PTFE                          |                               |                             |          |                          |                  |
| Bearing Pier P <sub>1</sub> -D <sub>0</sub> -all comp. |                               |                             |          |                          |                  |
|                                                        |                               | 3X                          | 250 =    | 750 T                    |                  |
|                                                        |                               | <del>1000</del><br>12103/26 |          | <del>2</del><br>12-03-28 |                  |
|                                                        |                               | J.E                         |          | A.E                      |                  |
| 16. > S/F and placing HYSD bar                         |                               |                             |          |                          |                  |
| reinforcement for AB-A <sub>1</sub> to P <sub>1</sub>  |                               |                             |          |                          |                  |
| main girder and cross girder                           |                               |                             |          |                          |                  |
| in super str. + D <sub>0</sub> -all                    |                               |                             |          |                          |                  |
| comp. Job                                              |                               |                             |          |                          |                  |
| main girder                                            |                               |                             |          |                          |                  |
| 28mm φ →                                               | 18X                           | 20.46X                      | @ 4.84 = | 1782.48 kg               |                  |
|                                                        | 10X                           | 20.46X                      | @ 4.84 = | 990.26 "                 |                  |
|                                                        | 6X                            | 21.928X                     | @ 4.84 = | 636.79 "                 |                  |
|                                                        | 4X                            | 20.162X                     | @ 4.84 = | 390.34 "                 |                  |
|                                                        | 4X                            | 17.862X                     | @ 4.84 = | 345.81 "                 |                  |
| Continuation                                           |                               |                             |          | C.O = 4145.68 kg         |                  |



| Particulars           | Details of actual measurement |         |         |       | Contents of area |
|-----------------------|-------------------------------|---------|---------|-------|------------------|
|                       | No.                           | L.      | B.      | D.    |                  |
|                       |                               |         |         | B.F = | 4145.68 kg       |
|                       | 4X                            | 15.404X | @4.84 = |       | 298.22 "         |
|                       | 4X                            | 12.944X | @4.84 = |       | 250.60 "         |
|                       | 2X                            | 21.770X | @4.84 = |       | 210.73 "         |
|                       | 2X                            | 19.162X | @4.84 = |       | 185.49 "         |
|                       | 2X                            | 15.704X | @4.84 = |       | 152.01 "         |
| 16mm $\phi$ ,         | 6X                            | 19.24X  | @1.58 = |       | 182.40 "         |
|                       | 6X                            | 19.26X  | @1.58 = |       | 182.58 "         |
| 6mm $\phi$ ,          | 66X                           | 19.26X  | @0.22 = |       | 279.66 "         |
|                       | 6X                            | 19.27X  | @0.22 = |       | 25.44 "          |
| 10mm $\phi$ ,         | 146X                          | 8.312X  | @0.62 = |       | 752.40 "         |
|                       | 36X                           | 8.56X   | @0.62 = |       | 191.06 "         |
|                       | 195X                          | 1.558X  | @0.62 = |       | 188.36 "         |
|                       | 83X                           | 8.328X  | @0.62 = |       | 428.56 "         |
|                       | 18X                           | 8.576X  | @0.62 = |       | 95.71 "          |
| 6mm $\phi$ ,          | 65X                           | 1.035X  | @0.22 = |       | 14.80 "          |
|                       | 130X                          | 0.750X  | @0.22 = |       | 21.45 "          |
|                       | 12X                           | 7.740X  | @0.22 = |       | 20.43 "          |
| <u>Cross Girders:</u> |                               |         |         |       |                  |
| 16mm $\phi$ →         | 8X                            | 5.546X  | @1.58 = |       | 70.10 "          |
|                       | 8X                            | 7.00X   | @1.58 = |       | 88.48 "          |
| 12mm $\phi$ →         | 4X                            | 5.438X  | @0.89 = |       | 19.36 "          |
|                       | 4X                            | 7.544X  | @0.89 = |       | 26.86 "          |
|                       | 4X                            | 7.588X  | @0.89 = |       | 27.01 "          |
|                       | 20X                           | 5.518X  | @0.89 = |       | 98.22 "          |
| 20mm $\phi$ →         | 6X                            | 6.380X  | @2.47 = |       | 94.55 "          |
|                       |                               |         |         | C.V = | 8050.16 kg       |

Continuation





| Particulars                       | Details of actual measurement |         |          |                           | Contents of area |
|-----------------------------------|-------------------------------|---------|----------|---------------------------|------------------|
|                                   | No.                           | L.      | B.       | D.                        |                  |
| 12mm $\phi$ $\rightarrow$         | 81X                           | 7.252X  | @ 0.89 = |                           | 522.797 kg       |
|                                   | 88X                           | 5.300X  | @ 0.89 = |                           | 415.096 "        |
|                                   | 84X                           | 5.300X  | @ 0.89 = |                           | 396.228 "        |
| 16mm $\phi$ $\rightarrow$         | 176X                          | 2.325X  | @ 1.58 = |                           | 646.536 "        |
| 8mm $\phi$ $\rightarrow$          | 156X                          | 1.85X   | @ 0.40 = |                           | 115.440 "        |
|                                   | 22X                           | 19.60X  | @ 0.40 = |                           | 172.480 "        |
|                                   | 24X                           | 19.512X | @ 0.40 = |                           | 187.315 "        |
|                                   | 21X                           | 19.270X | @ 0.40 = |                           | 184.992 "        |
|                                   | 10X                           | 19.270X | @ 0.40 = |                           | 77.080 "         |
|                                   | 10X                           | 19.270X | @ 0.40 = |                           | 77.080 "         |
|                                   | 16X                           | 1.700X  | @ 0.40 = |                           | 10.880 "         |
|                                   | 8X                            | 19.27X  | @ 0.40 = |                           | 61.664 "         |
|                                   | 130X                          | 1.656X  | @ 0.40 = |                           | 86.112 "         |
|                                   |                               |         |          |                           | 2953.70 kg       |
|                                   |                               |         |          |                           | 00, 2.954 kg.    |
|                                   | 16                            | 04/25   | 16       | A.E                       |                  |
|                                   |                               | 5E      |          |                           |                  |
| 12. > P/V and Laying Rec 4-30 2nd |                               |         |          |                           |                  |
| Deck Slab & railing do-af comp.   |                               |         |          |                           |                  |
| Slab $\rightarrow$                | 1X                            | 18.750X | 8.45X    | $(0.130 + 0.250 + 0.130)$ |                  |
|                                   |                               |         |          | $\frac{3}{3}$             |                  |
|                                   |                               |         |          |                           | = 26.9343        |
| Railing $\rightarrow$             | 2X                            | 18.750X | 0.475X   | 0.275                     | 4.898 "          |
|                                   |                               |         |          |                           | 31.82843         |
|                                   | 17                            | 04/25   | 17       | A.E                       |                  |
|                                   |                               | 5E      |          |                           |                  |

Continuation

Continuation





| Particulars                                        | Details of actual measurement |     |      |     | Contents of area |
|----------------------------------------------------|-------------------------------|-----|------|-----|------------------|
|                                                    | No.                           | L.  | B.   | D.  |                  |
|                                                    |                               | B.F | —    | Rs. | 11,76,233=00     |
| <u>7</u><br><u>10</u> > S/F and Placing HYSD       |                               |     |      |     |                  |
| Bar in bound                                       |                               |     |      |     |                  |
| — Do — all comp job.                               |                               |     |      |     |                  |
| 80.149 M.T                                         | vide                          | THB | P-65 |     |                  |
| 4.539 M.T                                          | "                             | "   | P-4) |     |                  |
| 84.688 M.T                                         |                               |     |      |     |                  |
| Admit → 84.630 M.T                                 |                               |     |      |     |                  |
| @ Rs. 77975.04/M.T                                 |                               |     |      | Rs. | 65,99,028=00     |
| <u>8</u><br><u>04</u> > P/v steel liner 6mm        |                               |     |      |     |                  |
| thick — Do — all comp job.                         |                               |     |      |     |                  |
| 14.20 M.T                                          | vide                          | THB | P-65 |     |                  |
| @ Rs. 1,06,749.53/M.T                              |                               |     |      | Rs. | 15,15,843=00     |
| <u>9</u><br><u>05</u> > Bored cast-in-place        |                               |     |      |     |                  |
| M-35 — Do — all comp job.                          |                               |     |      |     |                  |
| 584.00 M                                           | vide                          | THB | P-65 |     |                  |
| @ Rs. 18,656.09/M                                  |                               |     |      | Rs. | 1,08,95,157=00   |
| <u>10</u><br><u>03</u> > Pile load test on initial |                               |     |      |     |                  |
| and routine load test                              |                               |     |      |     |                  |
| — Do — all comp.                                   |                               |     |      |     |                  |
| 1750.00 M.T                                        | vide                          | THB | P-65 |     |                  |
| @ Rs. 300.00/M.T                                   |                               |     |      | Rs. | 5,25,000=00      |
| <u>11</u><br><u>53</u> > Pile Load test Lateral    |                               |     |      |     |                  |
| Load test — Do — all comp.                         |                               |     |      |     |                  |
| 50.00 M.T                                          | vide                          | THB | P-65 |     |                  |
| @ Rs. 5000.00/M.T                                  |                               |     |      | Rs. | 2,50,000=00      |
|                                                    |                               | C.V | —    | Rs. | 2,09,61,261=00   |

Continuation



| Particulars                                       | Details of actual measurement |     |      |       | Contents of area |
|---------------------------------------------------|-------------------------------|-----|------|-------|------------------|
|                                                   | No.                           | L.  | B.   | D.    |                  |
| B.F                                               | —                             | —   | —    | 3,03  | 13,760 = W       |
| 21/19 S/F and Placing HYSD bar                    |                               |     |      |       |                  |
| AB - A <sub>2</sub> to P <sub>2</sub> Main girder |                               |     |      |       |                  |
| Cross Girder - do - all comp.                     |                               |     |      |       |                  |
| 8.56 M.T                                          | vide                          | TMB | P-73 |       |                  |
| 8.56 M.T                                          | "                             | "   | P-78 |       |                  |
| 8.56 M.T                                          | "                             | "   | P-82 |       |                  |
| 2.954 M.T                                         | "                             | "   | P-75 |       |                  |
| 2.954 M.T                                         | "                             | "   | P-79 |       |                  |
| 31.588 M.T                                        |                               |     |      |       |                  |
| @ R. 78, 418 62/M.T                               |                               |     |      |       | R. 2477,087 = W  |
| 22/18 P/V and Laying Recct-30                     |                               |     |      |       |                  |
| Grade 20 super slt                                |                               |     |      |       |                  |
| do - all comp. 15B                                |                               |     |      |       |                  |
| 52.21 M <sup>3</sup>                              | vide                          | TMB | P-74 |       |                  |
| 31.828 M <sup>3</sup>                             | vide                          | "   | P-75 |       |                  |
| 52.21 M <sup>3</sup>                              | "                             | "   | P-78 |       |                  |
| 31.828 M <sup>3</sup>                             | "                             | "   | P-79 |       |                  |
| 52.21 M <sup>3</sup>                              | "                             | "   | P-82 |       |                  |
| 220.286 M <sup>3</sup>                            |                               |     |      |       |                  |
| @ R. 10,666 52/M <sup>3</sup>                     |                               |     |      |       | R. 23,49,685 = W |
| 23/14 Providing weep holes 20                     |                               |     |      |       |                  |
| 101 mg wall & return wall                         |                               |     |      |       |                  |
| do - all comp. 15B                                |                               |     |      |       |                  |
| 92.50 nos                                         | vide                          | TMB | P-80 |       |                  |
| @ R. 153.80 each                                  |                               |     |      |       | R. 14,150 = W    |
| C.D                                               | —                             | —   | —    | 35,54 | 682 = W          |

Continuation

